

CESAB PRODUCT RANGE

Counterbalanced and Warehouse Equipment






COUNTERBALANCED

4-wheel engine trucks torque converter






M315 - 318

 1.5t-1.8t
 6970 mm
 DIESEL / LPG






M320 - 325

 2.0t-2.5t
 6970 mm
 DIESEL / LPG






M330 - 335

 3.0t-3.5t
 6970 mm
 DIESEL / LPG

4-wheel engine trucks hydrostatic






Drago 150 - 180 - 200

 1.5t-1.8t-2.0t
 6170 mm
 DIESEL / LPG






Drago H 250 - 300 - 350

 2.5t-3.0t-3.5t
 7960 mm
 DIESEL / LPG






Drago E 250 - 300- 350

 2.5t-3.0t-3.5t
 7960 mm
 DIESEL / LPG



Drago 400 - 450 - 500




 4.0t-4.5t-5.0t
 6650 mm
 DIESEL

COUNTERBALANCED

3-wheel electric trucks






BIT 800 - 1000 - 1200

 0.8t - 1.0t - 1.2t
 5965 mm
 24V / 800 Ah






B210 - 213 - 215

 1.0t - 1.25t - 1.5t
 6470 mm
 24V / 1000 Ah






B315 - 316 - 316L - 318 - 318L - 320

 1.5t - 1.6t - 1.8t - 2.0t
 7470 mm
 48V / 750 Ah

4-wheel electric trucks






B415 - 416 - 416L - 418 - 418L - 420

 1.5t - 1.6t - 1.8t - 2.0t
 7470 mm
 48V / 750 Ah






B620 - 625 - 625L - 630 - 630L - 635

 2.0t - 2.5t - 3.0t - 3.5t
 6500 mm
 80V / 700 Ah






Mak 400 - 450 - 500

 4.0t - 4.5t - 5.0t
 7450 mm
 80V / 775 Ah

Compact electric trucks



cenTAURO 48 160L - 200L

 1.6t - 2.0t
 6970 mm
 48V / 840 Ah






cenTAURO 80 250 - 300

 2.5t - 3.0t
 6860 mm
 80V / 735 Ah

Heavy duty electric truck



B860 - 870 - 885



 6.0t - 7.0t - 8.5t
 6450 mm
 80V / 1250 Ah

WAREHOUSE EQUIPMENT

Hand pallet trucks



CE200 - 230 - 300

-  2.0t - 2.3t - 3.0t
-  The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model.






CE200ST

-  2.0 t
-  Stainless steel version



CE100HL - 100HLE

-  1.0 t
-  810 mm
-  Manual and electric scissor lifters.

Powered pallet trucks






P113

-  1.3 t
-  24V / 63 Ah






P214 - 216 - 218 - 220 - 225

-  1.4t - 1.6t - 1.8t - 2.0t - 2.5t
-  24V / 300 Ah
-  Optional operator platform available for P220.







P320 - 324

-  2.0t - 2.4t
-  24V / 620 Ah
-  The P320 is also available as a high performance version (8.5 km/h). The P324 is also available with power steering.

Reach trucks







R212 - 214 - 216

-  1.2t - 1.4t - 1.6t
-  8500 mm
-  48 V / 620 Ah
-  Also available as a cold store version as well as drive-in version with narrow overhead guard.



R314 - 316 - 318 - 320 - 325

-  1.4t - 1.6t - 1.8t - 2.0t - 2.5t
-  12500 mm
-  48V / 930 Ah
-  Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Powered stacker trucks



S110 - 110S

- 1.0t
- 2000 mm
- 24 V / 63 Ah
- S110S: straddle support arm version.



S208L

- 0.8 t
- 1580 mm
- 24 V / 230 Ah
- Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.



S210 - 212 - 214

- 1.0t - 1.2t - 1.4t
- 4755 mm
- 24V / 300 Ah
- Optional operator platform available.



S212S

- 1.2 t
- 4755 mm
- 24 V / 300 Ah
- Straddle support arms. Optional operator platform also available.



S212L - 214L

- 1.2 t - 1.4 t
- 4755 mm
- 24V / 300 Ah
- Elevating support arms. Optional operator platform available.



S220D

- 1.0t
- 2100 mm
- 24 V / 300 Ah
- Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.



S313 - 316 - 320

- 1.25t - 1.6t - 2.0t
- 5400 mm
- 24V / 425 Ah
- Also available as a walkie version (without platform and longer tiller arm).



S313L - 316L - 320L

- 1.25t - 1.6t - 2.0t
- 5400 mm
- 24V / 425 Ah
- Elevating support arms. Also available as a walkie version (without platform and longer tiller arm).



S314S

- 1.35 t
- 5400 mm
- 24V / 425 Ah
- Adjustable straddle support arms. Also available as a walkie version. (Without platform and longer tiller arm.)

Legend

Rated capacity	Additional info
Maximum lifting height	Fuel type
Maximum battery capacity	Nominal draw-bar pull

